

# Handheld Scanners

## Z-3060 *Sniper*

Handheld Omnidirectional Laser Scanner



### Features

- **Support both Omnidirectional and Single-Line scanning**
  - Button switch in between omnidirectional and single-line scanning
- **Aggressive scanning performance**
  - Powerful 20-line laser yields 1400 scans per second for omnidirectional scanning; 74 scans per second for single-line scanning
- **Z-SCAN technology**
  - ZEBEX proprietary real-time hardware decoding ensures instant recognition and decoding of the most popular 1D barcodes
- **Ergonomic and rugged design as well as an adjustable stand**
  - ABS plastic construction for heavy-duty use
  - An adjustable stand to meet varied operation requirements
- **Flexible communications**
  - Multi-interfaces include keyboard, RS-232C, USB and wand



### Applications

Post Office  
Administration  
Inventory control  
Retail  
Healthcare  
Manufacturing

Nevertheless, dreaming of having omnidirectional and single-line scanning capabilities on one scanner and yet not compromising on its size? The answer is *Sniper*, Z-3060, a handheld scanner on an adjustable stand.

In any orientation, *Sniper* detects and activates scanning omnidirectional barcode automatically. Or, by pushing one single button, *Sniper* turns to a single-line reader. Just believe this simple operation can meet sophisticated works!

Medium-scale retailers, pharmacies, specialty shops, post offices, convenience stores, warehouses and more stores will be benefited from this detailed-designed scanner.

Whenever scanning small items or large bulky items, on the counter or off the counter, and by handheld or hands-free, *Sniper* fulfills all kinds of operating needs. Featured trouble-free operations, dual scanning capabilities and stylish ID all together serve as a shining reliable tool partner, *Sniper*.


 **ZEBEX**




## Specifications

OPERATIONAL	
Light Source	650 nm visible laser diode (VLD)
Depth of Field	0 - 200 mm for UPC/EAN 100%
Scan Pattern	5 directions of scan field
Scan Rate	Omnidirectional 1,400 scans per second; Single-line 73 scans per second
Number of Scan Lines	20
Minimum Bar Width	5 mil @ PCS 90%
Print Contrast	30% @ UPC/EAN 100%
Indicators (LED)	Three-color LED (blue, red & white)
Beeper Operation	Programmable tone and volume
System Interfaces	Keyboard wedge, RS-232, USB, wand emulation
PHYSICAL	
Height	240.80 mm
Depth	151.20 mm
Width	100.00 mm
Weight	245g (stand excluded); 560g (with stand)
Cable	Standard 2m straight
POWER	
Input Voltage	5 VDC±10%
Power Consumption	1.0 watts
Operation Current	200 mA typical
REGULATORY	
Laser Class	CDRH class IIa; IEC 60825 class 2
EMC	CE EN55022 B, FCC part 15 class B, VCCI, BSMI
ENVIRONMENTAL	
Operating Temperature	0°C - 40°C (32°F - 104°F)
Storage Temperature	-20°C - 60°C (-4°F - 140°F)
Humidity	5% - 90% RH (no dewing allowed)
Ambient Light Injection	Up to 4,500 LUX (fluorescence)
Shock	Designed to withstand 1.5m drops

## Dimensions



## Scan Field



\* Product availability & specifications depend on territory market strategy; all are subjects to change without prior notice.  
 \*\* ZEBEX is the trademark of ZEBEX INDUSTRIES INC.; all rights reserved.